



Zecks Power Co., Ltd.

7F, NO.1-1, Ln.530, Zhongzheng N. Rd., Sanchong City, Taipei, Taiwan, R.O.C.
Tel : 886-2-29836088 Fax : 886-2-29838388 E-mail : zecks@seed.net.tw

Specification of ATX Switching Power Supply

Model No. ZKS-525A

【Total Wattage 250W】

Prepared By	Designed By	Approved By	Issued By

1. INPUT

1.1 AC Input : 115V (90V ~ 135V) ; 230V (180V ~ 260V)

Voltage selector by slide switches

1.2 AC Input Current : 115Vrms / 8A ; 230Vrms / 4.5A

(@ without AC Outlet)

1.3 Brown Out Voltage : 95VAC max. @ 60Hz.

1.4 Inrush Current : 30A max. / 115V , 15A max. / 230V

(at 25°C ambient cold start)

2. DC OUTPUT :

◆◆◆◆◆◆	V1	V2	V3	V4	V5	V6
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
Max. Current	14A (I1)	25A (I2)	10A	0.5A	1A	0.8A
Min. Current	0A	2A	1A	0A	0A	0A
Load Regulation	5%	5%	5%	10%	10%	5%
Line Regulation	1%	1%	1%	2%	2%	1%
Ripple & Noise	50mv	50mv	100mv	100mv	120mv	50mv
* * * * *	Total 125W Max.		* * *	* * *	* * *	* * *
			*	*	*	*

$$(V1 \cdot I1) + (V2 \cdot I2) < 125W$$

Note : A low pass filter shall be added to outputs during measurement. (EXP. : 0.47uF Tan-cap. & 0.1uF Ceramic-cap.)

3. OVERALL PERFORMANCE

3.1 Total Output Power : 250W

3.2 Efficiency : 78% min.

3.3 Power Up Time : < 16ms for +5V output voltage.

3.4 Hold Up Time : 8ms min.

3.5 Power Good Time : The PWR-GOOD signal will not be higher than 100 - 500 ms after the +5V output stabilizes at its operating value when the unit is turn on.

3.6 Power Fail Signal : The TTL compatible signal will go down at least 1 ms before +5V below 4.75V

3.7 Switching Frequency : 30KHz Typical.

3.8 Temperature coefficient : +0.05% per°C

3.9 PS on Signal : TTL compatible signal (active low)

4. PROTECTION FEATURES

- 4.1 Over Voltage Protection, DC +5V output from 5.5V ~ 6.5V
- 4.2 Over Load Protection, Total output 110% Min. ~ 140% Max.
- 4.3 Short Circuit, Latch off

5. ENVIRONMENTAL

- 5.1 Operation Temperature : 0°C ~ 50°C
- 5.2 Cooling : Forced air ventilation by DC fan.
- 5.3 Fan type : Ball Bearing FAN
- 5.4 Humidity : 10% ~ 90% RH
- 5.5 Storage Temperature : -20°C ~ 80°C
- 5.6 Storage Humidity : 5% ~ 90% RH
- 5.7 Altitude : 10,000 ft max.

6. SAFETY APPROVAL

UL 1950 ; cUL ; TUV EN60950 ; Nemko ; Fimko ; CB ; CE

7. ELECTROMAGNETIC COMPATIBILITY :

FCC Part 15, subjecting, class B ; CISPR-22, class B

8. DIELECTRIC WITHSTAND (HI-POT) TEST

- 8.1 Primary to Secondary : 1800VAC -- 3 Sec. (5mA cut - off)
- 8.2 Primary to Ground : 1800VAC -- 3 Sec. (5mA cut - Off)
- 8.3 Leakage Current < 3.5mA at input 230V~ 60Hz

9. INSULATION RESISTANCE

Input to Output : 60M Ω min. ; Input to Ground : 60M Ω min.

10. RELIABILITY : MTBF 100,000 hours @ 25°C ambient.

11. SHOCK AND VIBRATION

Operating : The power supply shall not suffer damage, or subsequently Fail to perform as specified, when subjected to a shake of 5 Gs for 11 mS, with a 1/2 sine wave for each of the Perpendicular axes X Y and Z.

12. MECHANICAL : L150 * W140 * H86 mm